



ALLBÄCK LINSEED OIL PAINT – QUALITY CONTROL FOR HANDLING, USE AND MAINTENANCE

Allbäck Linoljeprodukter AB
Balkåkravägen 18
271 91 Ystad, Sweden

Product name: **Allbäck** Linseed Oil Paint
Binder: **Allbäck** cleaned, boiled and matured linseed oil
Thinner: If necessary, **Allbäck** cleaned boiled linseed oil, max 5%

The Linseed Oil Paint contains only cleaned boiled linseed oil, titanium dioxide, iron oxides, cromoxid green ultramarine and chalk. Where required, add 10-15% max 20% Allbäck pure zinc paint to all colours. The paint is solvent-free and must never be thinned with solvents.

BUILDING MATERIAL ASSESSMENT -GREEN ARROW SUNDA HUS -A

Surface	The paint may be used on all clean, dry surfaces , exterior and interior. Max. moisture content 15%. May be applied in direct sunlight. Impregnate dry wood and cracks with raw linseed oil before painting.
Application	Stir the paint thoroughly. Brush roll or spray (high pressure, small nozzle).
Cleaning	Ammonia, Allbäck Linseed Soap. Wash hands and brushes with Linseed Soap and water.
Storage	Store brushes suspended in raw linseed oil (never in water).
Keeping	May be kept indefinitely, even below freezing.
Coverage	15–20 m ² per litre. Each coat should <u>cover the surface completely</u> and be painted in <u>even</u> layers. Apply the same paint in at least three coats on new exterior surfaces. Thickness approximately 100 microns per coat . Apply four coats to particularly exposed surfaces.
Drying time	Approx. 24 hours at room temperature, ventilation, light and low humidity, 50% RH.
Transport	No restrictions – not hazardous goods

Risk of self-ignition – always soak rags in water and discard!

Waste management - No specific restrictions.

Paint remnants can be used down to the last drop. Combine any remaining paint and use as first coat or mix with about 30% water to make an emulsion for concrete floors, brick walls or wood.

Tins can be discarded as normal metal waste. In Sweden, we have an agreement with REPA on recycling.

Technical specifications, safety data sheets and emission tests

These are available on our website www.allbackpaint.com

VOC – Allbäck Linseed Oil Paint contains <1.1% VOC

Cleaning & Maintenance

Linseed Oil Paint is elastic and thus absorbs more dirt in the initial phase. After a few years, the pigment grains start to fall out and the paint becomes “self-cleaning”.

Assuming that the surface has been given three full coats of paint, dirt and mould can be cleaned off using Allbäck Linseed Soap. Avoid too high pH. Mix the Linseed Soap with water until it foams. Clean the surface using a sponge or a brush. Rinse thoroughly and allow to dry. When the surface turns matt and starts to become chalky, treat with Boiled Linseed Oil or Linseed Oil Wax or a coat of Linseed Oil Paint. The need for maintenance varies considerably depending on the original treatment, exposure to the elements and other stresses. Interior surfaces have much longer maintenance intervals and retain their shine for many years. Touch-up work will have a different shine initially.

Comments:

The results of applying Allbäck Linseed Oil Paint depend on the structure, surface, preparation, temperature, humidity, ventilation, light and method of application. **Detailed instructions** can be found in the **Concise Handbook** on our website www.allbackpaint.com.

Always paint a test area first. In the event of a complaint, please include your documentation.

Treated surface.....
With paint type..... Date.....

I/We have read the instructions, carried out the preparatory work and painted.....